


Ecoguss project drain DN 100, vertical, Design cover





Article information

Item no.: 48411.63 GTIN: 4026092053096

Price group: 40

Advantages

- High-tech Ecoguss composite material
- Highest fire protection standards
- Scientifically confirmed sound protection effect

Description

The Ecoguss project drain with connection flange is used for point drainage and is equipped with a removable odour trap as well as a lip seal and a temporary protective cover. The recyclable composite material Ecoguss meets the highest noise protection requirements, is temperature-resistant, resistant to aggressive media, and has a permanently corrosion-free surface. It is also briefly flammable from 100 to 400 degrees Celsius. The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary.

Variant

System: 125

Waterproofing layer on the upper section: Connection flange Waterproofing layer on the drain body: Connection flange

Sealing water height: 50 mm

General characteristics

Standard: EN 1253-1 Nominal size (DN): 100 Outer diameter (OD): 110 mm

Inlet max. scoring (DN): Z-19.53-2414,Z-19.17-1719

Dimensions

Net weight: 1,85 kg
Gross weight: 2,22 kg
Diameter: 135 mm

Vertical adjustment: vertically adjustable upper section



Length:135 mmWidth:135 mmPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height

Tank/drain body

Number of outlets: 1

Material of drain body: Ecoguss System: vertical

Coverage features

Type of cover: Design cover

Cover material: Stainless steel 14301

Colour of cover:silverWidth of cover:120 mmHeight of cover:16 mmLength of cover:120 mm

Frame material: Stainless steel 14301

Cover locking: Lock & Lift Load class: L 15 (EN 1253-1)

Grating colour: Kessel

Slip resistance class: R9 according to DIN 51130; C according to DIN

51097

Rim length: 132 mm
Rim material: 132 mm
Max. flooring height: 16 mm

Upper section: vertically adjustable

Upper section material: ABS
Odour trap: included